



ENGINE OIL DRAIN VALVES

ACCESSORIES

LC-SERIES LEVER CLIPS



LC-10, LC-15 shown in locked position

LC-10 & LC-15 Lever Clips attach to the valve stem and lock the actuating lever in the closed position. Choose if you desire extra security over and above what the standard locking lever mechanism offers.



LC-10, LC-15

LC-10 fits all F-Series valves
LC-15 fits all T & FG valves

SH-10 SOCKET



The **SH-10 Socket** is used to securely attach a 3/8" hose to S and SW series valves. Use with the optional **F-Hose** to direct the oil flow into a receptacle when the drain port location is obstructed or in a difficult to reach area.



SH-10 attached to F106S & F-Hose

To remove from the nipple, gently grasp and bend the hose and socket until it unseats.

HC-SERIES SECURITY CLIPS



HC-58

HC Hose Clips firmly secure the lever in the locked position for extra safety and security. If you operate your vehicle on rough terrain or in conditions where objects may strike the oil drain port location (i.e. logging, off-road, farming) we recommend installing a hose clip.



HC-58 shown on F-106

HC-58 fits F Series valves
HC-34 fits T and FG series valves

90° L NIPPLE EXTENSIONS



L-001


L shaped plastic 90° extensions are specifically designed to accept a hose for efficient and clean oil drainage when a directional flow is desired or when the drain port location is obstructed or in a difficult to reach area.



L-002

The **L-001** fits 3/8" nipples on FN, FS & FSW series valves.
The **L-002** fits 5/8" nipples on TN and FG series valves.

F-HOSE



3/8" X 3' Hose

The **F-Hose** drain hose fits FN, FS and FSW series valves with 3/8" nipples. 3' length allows a user to easily direct the oil flow into a receptacle. Especially useful when the drain port location is obstructed or in a difficult to reach area.



F-Hose attached to L-001 & F106S

When using with S & SW series valves we recommend using with the optional **SH-10** socket or **L-001** 90° L extension.

NIPPLE CAPS



The vinyl corrosion resistant **F & M Caps** slip over the nipple end preventing unwanted material from collecting inside the nipple while under use.



F-Cap shown on F106N

F-CAP fits F-Series valves with 3/8" nipples.
M-Cap fits T & FG valves with 5/8" diameter nipples.

www.fumotousa.com

Fumoto Engineering of America, Inc.

3330 Industrial Drive, Santa Rosa CA 95403

707-545-7020 • (800) 918-3406 • Fax: 707-546-1910